



GILLETTE GENERATORS



PORTABLE / GPE-75EH

GENERATOR MODEL	GPE-75EH
MAX. KW @ 1 PH.	7.5
PRIME KW @ 1 PH.	6.5
PRIME AMPS @ 120 V.	54
PRIME AMPS @ 240 V.	27
GENERATOR REGULATION	5 % VOLTAGE REGULATION ON SINGLE PHASE GEN-SETS.
FREQUENCY REGULATION	5 %, (3 HERTZ) FREQUENCY REGULATION FROM NAME PLATE RATING
"KLEEN-POWER"™	ELECTRICAL WAVEFORM DISTORTION IS LIMITED TO JUST 6 % ON ALL GEN- PRO GEN-SETS
ENGINE MODEL (WARRANTY)	HONDA GX390 O.H.V. (3 YEARS)
ENGINE START METHOD	12VDC ELECTRIC & ROPE RECOIL
ENGINE HP @ 3600 RPM	13 HP
ENGINE DISPLACEMENT	1 CYLINDER, 23.7 CU. IN. (390 CC)

GENERATOR MODEL	GPE-75EH
ENGINE AIR CLEANER	HEAVY DUTY, LOW PROFILE, DUAL ELEMENT FILTERS
ENGINE FUEL TANK	8 GAL. (30.2 L.) METAL FUEL TANK WITH GAUGE, TWIST-CAP, & SLOSH VALVE
ENGINE OIL SYSTEM	FORCED SPLASH
LOW OIL PROTECTION	AUTOMATIC ENGINE SHUTDOWN PROTECTION AT LOW OIL LEVEL
db(A) AT 7 METERS	78
3/4 LOAD RUN TIME (HRS)	8.4
FUEL USE, GAL/ LTR/HR	0.95 / 3.56
MOTOR START POWER	2 1/2 HP, CODE G ELECTRIC MOTOR
CRANE PICK-UP HOOK	OPTIONAL EQUIPMENT : CENTRAL PICK-UP ON TOP OF GEN-SET
2-WHEEL DOLLY KIT	OPTIONAL EQUIPMENT : COMPLETE WITH (2) HANDLES AND "NEVER GO FLAT" WHEELS
MAINLINE CB	30 AMP, 2 POLE MAGNETIC MAIN LINE CIRCUIT BREAKER
HOUR METER	RUN TIME HOURS, PLUS (3) MAINTENANCE ALERTS: 25 HOUR CHANGE OIL, 25 HOUR CHANGE OIL FILTER, 25 HOUR SERVICE AIR FILTER
POWER RECEPTACLES	(4) NEMA 5-15R 120 VOLTS, AND (1) L-14-30R 240 VOLTS RECEPTACLES
PROTECTIVE ROLL FRAME	RUGGED 1-1/4" ROUND ROLL FRAME, PROTECTING ENTIRE GEN-SET
LENGTH, INCHES	31
WIDTH, INCHES	25
HEIGHT, INCHES	27.5
SHIP WEIGHT, LBS.	277
CU. FEET SHIP BOX	20