

# MTD EF TEES

PE4710 | 4.7MM TERMINALS | ASTM F1055, F2897, D2513 & D3350



ISCO's MTD EF Tees are designed to be as safe and efficient as possible. With a variety of sizes, both size-on-size and reducing, each tee includes integrated stab depth indicators to ensure proper stab depth. As a universal fitting, our couplings can be fused, 40v fusion, via barcode, dedicated resistor, or manually.

- Universal fittings can be fused in barcode, resistor (dedicated) or manual modes
- 40V Fusion
- Molded from virgin PPI-Listed PE4710 / PE100 Resin
- Compliant with ASTM F2897 traceability standards

PART NO.	SIZE [in]	A [min]	B [min]	C [min]	D [min]	L [min]
TRI0255	¾ IPS	1.76	1.05	1.72	1.05	4.21
TRI0265	1 IPS	1.97	1.32	2.16	1.31	4.84
TRI0320	2 IPS	3.28	2.37	2.67	2.37	6.81
TRI0340	4 IPS	5.65	4.50	3.46	4.50	10.90
TRI0342	4 x 2 IPS	5.65	4.50	2.55	2.38	10.90
TRI0360	6 IPS	8.11	6.63	4.72	6.63	14.96
TRI0370	6 x 4 IPS	8.11	6.63	3.46	4.50	14.96
TRI0380	8 IPS	10.68	8.61	5.39	8.63	18.46
TRI0385	8 x 4 IPS	10.68	8.61	3.46	4.50	18.46
TRI0390	8 x 6 IPS	10.68	8.61	4.72	6.63	18.46

