

MTD

TAPPING TEE CUTTERS

MTD TRIFUSION HIGH-VOLUME AND STANDARD TAPPING TEES

MTD Tapping Tee cutters are designed to be as efficient and safe as possible. The High-Volume Tapping Tee is equipped with a shutoff cutter that, once advanced back into the tapped hole, completely shuts off the flow of gas through the outlet. All cutters are bottom-loaded to prevent the possibility of the cutter rotating out of the top of the tapping tee.



HIGH-VOLUME TAPPING TEE CUTTER

High-Volume Tap Diameter:

2" mains : 1.34"Ø

3" thru 12" mains: 1.77"Ø

Tapping Torque:

High-Volume: 108.45 lb/ft

High-Volume Compatible Wall Thicknesses:

2" thru 8" mains : DR7 or thinner

12" mains: DR11 or thinner

5/8" Hex Drive



STANDARD TAPPING TEE CUTTER

Standard Tap Diameter:

1 ¼" mains : 0.76"Ø

2" thru 6" mains: 1.00"Ø

8" thru 12" mains: 1.77"Ø

Tapping Torque:

Standard: 21.6g lb/ft

Standard Compatible Wall Thicknesses:

1 ¼" thru 8" mains : DR7 or thinner

12" mains: DR11 or thinner

5/8" Hex Drive